



Metal Processing Co., Inc.

Specializing in Glass-to-Metal Seals

PIN END Condition & Style Configurations			
<p>Full Radius</p> <p><u>SR</u></p>	<p>Full Radius</p> <p><u>PREFERRED</u></p>	<p>Min. Radius 25% of Pin Diameter</p> <p>Blunt Tip Permissible to 50% of Pin Diameter</p> <p><u>OPTIONAL</u></p>	<p>.005 R (Burr-Free with Sharp Edges)</p> <p><u>SC</u></p>
<u>Spherical Radius (SR Options)</u>			
<p>Nail Head</p> <p><u>NH</u></p>	<p>Radius or SC (One End or Both Ends)</p> <p><u>STEPPED</u></p>	<p>Flat (Paddle)</p> <p><u>FLATTENED</u></p>	<p>.000 / .003 R, Burr-Free with Sharp Edges Permitted (for Wire Bonding)</p> <p><u>SC (90%)</u></p>
<p><u>TURRET</u></p>	<p><u>UPSET</u></p>	<p>Flat & Pierced (Paddle)</p> <p><u>FLATTENED & PIERCED</u></p>	<p>SMA (Bullet Nose)</p> <p><u>SMA</u></p>
			<p>90° Bend</p> <p><u>L-BEND</u></p>
<p><u>COMPOUND BEND</u></p>		<p>Additional Styles and Designs are available upon Request</p>	

Voice: 978-649-1289 • Fax: 978-649-2955
 sales@metproco.com • www.metproco.com

ISO 9001:2008 and AS9100 Certified